



CUSH-WRAP

Cushion Wrap

SERVICE: Provides protection from galvanic action between dissimilar metals, isolates pipe and absorbs sound and vibrations between pipe and mounting system.

MATERIAL: EPDM Elastomer

MAX TEMP: 300°F

ORDERING: Specify figure number. Cushion Wrap is supplied in 25' rolls.

COPPER TUBING TYPE L AND TYPE K		
NOMINAL PIPE SIZE	LENGTH OF CUSH WRAP	PLATED O.D. CLAMP SIZE
1/4	1 1/8	3/8
3/8	1 5/8	1/2
1/2	2	5/8
3/4	2 3/4	7/8
1	3 3/8	1 1/8
1 1/4	4 3/8	1 3/8
1 1/2	5 1/8	1 5/8
2	7 1/8	2 1/8
2 1/2	8 1/4	2 5/8
3	10 1/4	3 1/8
3 1/2	11 3/8	3 5/8
4	13 3/8	4 1/8
5	16 1/2	5 1/8
6	19 5/8	6 1/8
8	25 7/8	8 1/8



1. Cut appropriate length strip using the cutting schedule shown on left.
2. Place the pipe on the Cushion Wrap.
3. Insert the clamps in the strut.
4. Tighten the clamps.

STANDARD PIPE RIGID CONDUIT		
NOMINAL PIPE SIZE	LENGTH OF CUSH WRAP	PLATED O.D. CLAMP SIZE
1/4	1 3/4	3/4
3/8	2 1/8	7/8
1/2	2 3/4	1
3/4	3 3/8	1 1/4
1	4 1/4	1 1/2
1 1/4	5 1/4	1 7/8
1 1/2	6	2 1/8
2	7 1/2	2 5/8
2 1/2	9 1/8	3 1/8
3	11	3 5/8
3 1/2	12 5/8	4 1/4
4	14 1/4	4 3/4
5	17 1/2	5 7/8
6	20 7/8	6 7/8
8	27 1/8	8 7/8

