



FIG. 100

Split Ring Extension Hanger

- SERVICE:** For suspension of non-insulated, stationary piping services.
- MATERIAL:** Malleable Iron or 304/316 Stainless Steel
- FINISH:** Black or Electro-Galvanized
- STANDARDS:** MSS SP-58 Type 12, FS WW-H-171E Type 25
- ORDERING:** Specify figure number, pipe size, material and finish.



PIPE SIZE	PIPE OD	SCREW	A	B	C	D	WEIGHT EACH, LBS.	MAX REC. LOAD, LBS.
3/8	0.675	10 - 24	3/8	11/16	1 ¹³ / ₁₆	1 ³ / ₁₆	0.08	180
1/2	0.840	10 - 24	3/8	3/4	2 ¹ / ₈	1 ³ / ₁₆	0.10	180
3/4	1.050	10 - 24	3/8	7/8	2 ¹ / ₂	1 ⁹ / ₁₆	0.11	180
1	1.315	10 - 24	3/8	1 ¹ / ₈	2 ³ / ₄	2	0.15	180
1 ¹ / ₄	1.660	10 - 24	3/8	1 ⁵ / ₁₆	3 ³ / ₁₆	2 ³ / ₈	0.18	180
1 ¹ / ₂	1.900	10 - 24	3/8	1 ⁷ / ₁₆	3 ³ / ₈	2 ⁵ / ₈	0.21	180
2	2.375	10 - 24	3/8	1 ⁵ / ₈	3 ¹⁵ / ₁₆	3 ¹ / ₁₆	0.30	180
2 ¹ / ₂	2.875	1/4	1/2	2 ¹ / ₈	5 ³ / ₁₆	3 ¹³ / ₁₆	0.58	300
3	3.500	1/4	1/2	2 ¹ / ₂	5 ¹¹ / ₁₆	4 ⁵ / ₈	0.71	300
4	4.500	1/4	1/2	2 ⁷ / ₈	6 ³ / ₄	5 ⁹ / ₁₆	1.02	300

NOTE: Sizes 1/4", 3/8", 2 1/2", 3" and 4" are only available in hinged style, with the exception of stainless steel which is only available in two-screw style regardless of size.

