



**FIG. 200**

**Adjustable Clevis Hanger for Copper Tubing**

**SERVICE:** For the suspension of non-insulated stationary tubing services.  
**MATERIAL:** Carbon Steel  
**FINISH:** Copper Epoxy Coated (Copper-Gard)  
**STANDARDS:** MSS SP-58 Type 1, FS WW-H-171E Type 12  
**ORDERING:** Specify figure number and tube size.



TUBE SIZE	TUBE OD	A	B	C	E	F	BOLT	WEIGHT EACH, LBS.	MAX REC. LOAD, LBS.
1/2	0.625	3/8	1 7/8	2 3/16	1 1/8	1/2	1/4	0.12	150
3/4	0.875	3/8	1 3/4	2 1/8	1	1/2	1/4	0.12	250
1	1.125	3/8	1 13/16	2 5/16	1 1/16	1/2	1/4	0.12	250
1 1/4	1.375	3/8	2 1/8	2 3/4	1 5/16	3/4	1/4	0.12	250
1 1/2	1.625	3/8	2 1/2	3 1/4	1 3/4	15/16	1/4	0.18	250
2	2.125	3/8	2 15/16	4	2 3/16	1 1/16	1/4	0.24	250
2 1/2	2.625	1/2	4 7/8	5 3/4	3 3/8	2 1/16	1/4	0.58	350
3	3.125	1/2	4 1/2	6 1/8	3 7/16	2	1/4	0.60	350
4	4.125	1/2	5 7/8	7 7/8	4 3/4	2 9/16	5/16	1.02	400
5	5.125	5/8	5 7/8	8 3/4	4 3/4	1 5/8	3/8	1.68	550
6	6.125	5/8	6 1/16	9	4 3/4	1 1/2	3/8	1.84	550

