



**FIG. 538**

**Adjustable Pipe Saddle Support w/ U-Bolt**

**FIG. 539**

**Adjustable Pipe Saddle Support w/ DI U-Bolt**

**SERVICE:** For general piping running close to the floor.  
**MATERIAL:** Carbon Steel or 304/316 Stainless Steel  
**FINISH:** Black or Hot-Dip Galvanized  
**STANDARDS:** MSS SP-58 Type 37/38  
**ORDERING:** Specify figure number, pipe size, L dimension, base plate hole size, material and finish. (Unit consists of saddle, nipple and reducer. Gussets will be added to supports for pipe sizes 8" and above. Welded base plate and pipe must be ordered separately.)



PIPE SIZE	PIPE SIZE A	B	C	D	DIMENSION E		WEIGHT EACH, LBS.	
					MIN.	MAX.	SADDLE ONLY	WITH REDUCER
2½	2½	3 <sup>7</sup> / <sub>16</sub>	8	1½	8 <sup>11</sup> / <sub>16</sub>	13 <sup>13</sup> / <sub>16</sub>	4.14	7.44
3	2½	3 <sup>11</sup> / <sub>16</sub>	8	1½	9	14 <sup>1</sup> / <sub>8</sub>	4.40	7.70
4	3	4 <sup>3</sup> / <sub>16</sub>	10	2½	9 <sup>5</sup> / <sub>8</sub>	15 <sup>1</sup> / <sub>4</sub>	5.83	13.39
5	3	4 <sup>13</sup> / <sub>16</sub>	10	2½	10 <sup>3</sup> / <sub>16</sub>	15 <sup>15</sup> / <sub>16</sub>	6.48	14.04
6	3	5 <sup>7</sup> / <sub>16</sub>	10	2½	10 <sup>13</sup> / <sub>16</sub>	16 <sup>7</sup> / <sub>16</sub>	10.24	17.80
8	3	6 <sup>15</sup> / <sub>16</sub>	10	2½	12 <sup>9</sup> / <sub>16</sub>	17 <sup>15</sup> / <sub>16</sub>	13.16	20.72
10	3	8 <sup>7</sup> / <sub>16</sub>	10	2½	13 <sup>3</sup> / <sub>4</sub>	19 <sup>5</sup> / <sub>8</sub>	17.23	24.79
12	3	9 <sup>15</sup> / <sub>16</sub>	10	2½	15 <sup>5</sup> / <sub>8</sub>	21	22.56	30.12
14	4	10 <sup>15</sup> / <sub>16</sub>	10	3	16 <sup>3</sup> / <sub>16</sub>	21 <sup>3</sup> / <sub>16</sub>	29.20	42.55
16	4	12 <sup>3</sup> / <sub>8</sub>	10	3	17 <sup>9</sup> / <sub>16</sub>	22 <sup>9</sup> / <sub>16</sub>	33.53	46.88
18	6	13 <sup>7</sup> / <sub>8</sub>	12	4	19 <sup>7</sup> / <sub>8</sub>	24 <sup>1</sup> / <sub>4</sub>	52.83	74.78
20	6	15 <sup>3</sup> / <sub>8</sub>	12	4	21 <sup>3</sup> / <sub>8</sub>	25 <sup>3</sup> / <sub>4</sub>	56.96	78.91
24	6	17 <sup>15</sup> / <sub>16</sub>	12	4	23 <sup>5</sup> / <sub>8</sub>	28	78.92	100.87
30	6	21 <sup>5</sup> / <sub>16</sub>	12	4	27 <sup>3</sup> / <sub>8</sub>	31 <sup>3</sup> / <sub>4</sub>	90.40	112.35
36	6	24 <sup>1</sup> / <sub>2</sub>	12	4	30 <sup>5</sup> / <sub>8</sub>	35	107.92	129.87

DI PIPE SIZE	PIPE SIZE A	B	C	D	DIMENSION E		WEIGHT EACH, LBS.	
					MIN.	MAX.	SADDLE ONLY	WITH REDUCER
3	2½	3 <sup>15</sup> / <sub>16</sub>	8	1½	9 <sup>1</sup> / <sub>8</sub>	14 <sup>1</sup> / <sub>4</sub>	4.52	7.82
4	3	4 <sup>5</sup> / <sub>16</sub>	10	2½	9 <sup>13</sup> / <sub>16</sub>	15 <sup>7</sup> / <sub>16</sub>	5.99	13.55
6	3	5 <sup>9</sup> / <sub>16</sub>	10	2½	11	16 <sup>5</sup> / <sub>8</sub>	10.50	18.06
8	3	7 <sup>1</sup> / <sub>8</sub>	10	2½	12 <sup>9</sup> / <sub>16</sub>	18 <sup>3</sup> / <sub>16</sub>	13.43	20.99
10	3	8 <sup>5</sup> / <sub>8</sub>	10	2½	13 <sup>15</sup> / <sub>16</sub>	19 <sup>9</sup> / <sub>16</sub>	16.81	24.37
12	3	10 <sup>3</sup> / <sub>16</sub>	10	2½	15 <sup>5</sup> / <sub>8</sub>	21 <sup>1</sup> / <sub>4</sub>	21.98	29.54
14	4	11 <sup>9</sup> / <sub>16</sub>	10	3	16 <sup>7</sup> / <sub>8</sub>	21 <sup>7</sup> / <sub>8</sub>	29.02	42.37
16	4	13 <sup>1</sup> / <sub>16</sub>	10	3	18 <sup>3</sup> / <sub>16</sub>	23 <sup>9</sup> / <sub>16</sub>	33.38	46.73
18	6	14 <sup>5</sup> / <sub>8</sub>	12	4	20 <sup>5</sup> / <sub>8</sub>	25	52.55	74.50
20	6	16 <sup>3</sup> / <sub>16</sub>	12	4	22 <sup>3</sup> / <sub>16</sub>	26 <sup>9</sup> / <sub>16</sub>	56.79	78.74
24	6	18 <sup>13</sup> / <sub>16</sub>	12	4	24 <sup>9</sup> / <sub>16</sub>	28 <sup>15</sup> / <sub>16</sub>	78.85	100.80
30	6	22 <sup>9</sup> / <sub>16</sub>	12	4	28 <sup>3</sup> / <sub>8</sub>	32 <sup>3</sup> / <sub>4</sub>	94.57	116.52
36	6	25 <sup>5</sup> / <sub>8</sub>	12	4	31 <sup>13</sup> / <sub>16</sub>	36 <sup>3</sup> / <sub>16</sub>	109.32	131.27

