



FIG. 855

Hangermate®+

SERVICE: For suspending threaded rod vertically overhead in pipe hanging, fire protection, electrical conduit and cable-tray applications.

MATERIAL: Carbon Steel

FINISH: Electro-Galvanized

APPROVALS: FM, UL

ORDERING: Specify figure number.

FIG #	SIZE #	TYPE	ROD SIZE	MOUNT DIRECTION	SCREW SIZE	LENGTH	WEIGHT EACH, LBS.
2211200	PFM2211200	CONCRETE	3/8	VERTICAL	1/4	1 5/8	0.07
2211260	PFM2211260	CONCRETE	3/8	VERTICAL	3/8	1 5/8	0.08
2211280	PMF2211280	CONCRETE	1/2	VERTICAL	3/8	2	0.13
7159	PFM2231200	STEEL	3/8	VERTICAL	1/4	1 1/2	0.075
7164	PFM2251300	WOOD	1/2	VERTICAL	5/16	2 1/2	0.082
7165	PFM2251100	WOOD	3/8	VERTICAL	1/4	2	0.073
7170	PFM2261100	WOOD	3/8	SIDE	1/4	2	0.073
7173	PFM2217173	CONCRETE	3/8	VERTICAL	1/4	1 1/2	0.070
7175	THD50234RH	CONCRETE	1/2	VERTICAL	1/2	2 3/4	0.082

NOTE: Refer to Dewalt Anchors & Fasteners, Hangermate®+ for maximum recommended loads and additional details. Refer to Simpson Strong-Tie, Titen HD for additional details on FIG #7175.

